

2020 COMMANDER™ XT™

HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok QE⁺ auto-locking front differential
- Double A-arm front suspension with sway bar
- Torsional Trailing arm Independent (TTI) rear suspension with external sway bar
- Intelligent Throttle Control (iTC™)
- Industry's exclusive Dual-Level™ cargo box
- 14-in. cast-aluminum wheels with 27-in. Maxxis Bighorn 2.0[†] tires
- 4,500-lb (2,041 kg) winch
- Heavy-duty front bumper
- Rugged bed rails
- Mudguards
- Analog / digital gauge



- Boreal Green / 800R / 1000R
- Black & Octane Blue / 800R / 1000R
- Mossy Oak[†] Break-Up Country Camo[†] / 1000R

| ENGINES | 800R | 1000R |
|----------------------|---|---|
| Type | 71 hp, Rotax® 799.9 cc, V-twin, liquid cooled | 92 hp, Rotax® 976 cc, V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI) | |
| Transmission | CVT, L / H / N / R / P, standard engine braking | |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok QE ⁺ auto-locking front differential | |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) | |

TIRES / WHEELS

| | |
|-------------|---|
| Front Tires | Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm) |
| Rear Tires | Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm) |
| Wheels | 14-in. (35.6 cm) cast-aluminum |

SUSPENSIONS

| | |
|------------------|--|
| Front Suspension | Double A-arm with sway bar / 10 in. (25.4 cm) travel |
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Torsional Trailing arm Independent (TTI) with external sway bar 10 in. (25.4 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |

DIMENSIONS / CAPACITIES

| | |
|------------------|---|
| L x W x H | 120.2 x 62.5 x 72 in. (305.4 x 158.8 x 182.9 cm) |
| Wheelbase | 75.8 in. (192.4 cm) |
| Ground Clearance | 11 in. (27.9 cm) |
| Dry Weight* | 1,291.4 lb (586 kg) |
| Rack Capacity | 600 lb (272 kg) Dual-Level cargo box Upper level: 400 lb (181 kg) Lower level: 200 lb (91 kg) |
| Storage Capacity | Total: 8.3 gal (31.6 L) Glove box: 4.5 gal (17.2 L) Under driver seat: 3.5 gal (13.1 L) (800R only) Center console: 0.3 gal (1.3 L) |
| Towing Capacity | 1,500 lb (680 kg) |
| Fuel Capacity | 10 gal (37.8 L) |

BRAKES

| | | |
|-------|--|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers | Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper | |

FEATURES

| | | | |
|------------|---|-------------------|--|
| Gauge | Multifunction analog / digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport mode, ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| Winch | 4,500-lb (2,041 kg) winch with roller fairlead | Lighting | 240 W from four 60-W projectors with tail lights / brake lights |
| Protection | Heavy-duty front bumper, mudguards, bed rails | Anti-theft System | Digitally Encoded Security System (D.E.S.S.™) |

WARRANTY

| | |
|----------|-----------------------------------|
| Factory | 6-months limited warranty |
| Extended | Up to 30 months B.E.S.T. coverage |

BEST PROTECTION ©2019 Bombardier Recreational Products Inc. (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

can-am.

Can-AmOffroad.com

