

# can-am

## DEFENDER MAX X mr HD10

2021

### HIGHLIGHTS

<b>TOUGH</b>	<ul style="list-style-type: none"> <li>• Heavy-duty Rotax® engine</li> <li>• Smooth, durable and responsive transmission</li> <li>• True Can-Am DNA with a strong identity</li> </ul>
<b>CAPABLE</b>	<ul style="list-style-type: none"> <li>• Work or ride with confidence</li> <li>• Meaningful and versatile functionality</li> <li>• Easy handling and capabilities</li> </ul>
<b>CLEVER</b>	<ul style="list-style-type: none"> <li>• Advanced comfort and intuitive cockpit with optimized visibility</li> <li>• Multifunction cargo box with sturdy tailgate and smart storage</li> <li>• 1 year maintenance-free and easy access to key maintenance components</li> </ul>
<b>PLATFORM FEATURES</b>	<ul style="list-style-type: none"> <li>• 115.5 in. wheelbase</li> <li>• 15 in. of ground clearance</li> <li>• Dynamic Power Steering (DPS™)</li> <li>• ECO™/ECO™ Off/Work modes</li> <li>• 2,500 lb towing capacity</li> <li>• Multifunction cargo box</li> <li>• Rear differential with Turf mode</li> </ul>
<b>SPECIFIC TO X mr PACKAGE</b>	<ul style="list-style-type: none"> <li>• 64 in. wide with arched A-arm</li> <li>• LED Signature</li> <li>• Smart-Lok® front differential</li> <li>• Strategically positioned engine air intake and CVT inlet/outlet</li> <li>• 14 in. cast-aluminum wheels</li> <li>• 30 in. ITP® Cryptid® tires</li> <li>• VERSA-PRO bolster bench seats, reinforced seat skin featuring X package trims and adjustable driver seat</li> <li>• HMWPE full skid plate</li> <li>• 4,500 lb (2,014 kg) winch</li> <li>• Heavy-duty front steel bumper</li> <li>• Aluminum rock slider</li> <li>• 7.6 in. digital display with keypad</li> <li>• Brake holding mechanism</li> </ul>

ENGINE	HD10
Type	82 hp/69 lb-ft, Rotax 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ Transmission with Quick Response System (QRS), Electronic Drive Belt Protection, lower gearing ratio and high-airflow ventilation with strategically positioned CVT air intake and exhaust, Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD TRAIL/4WD MUD with exclusive Smart-Lok® technology.
Driving Assistance	Electronic Hill Descent Control ECO™/ECO™ Off/Work modes
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched TTA/10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES & WHEELS	
Front Tires	ITP Cryptid® 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid® 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
	Brake holding mechanism



Mossy Oak® Break-Up Country Camo® / HD10

### DIMENSIONS & CAPACITIES

Chassis/Cage	Profiled cage, ROPS approved
Estimated Dry Weight	1,999 lb (907.7 kg)
L x W x H	161.9 x 64 x 82 in. (411.2 x 162.6 x 208.3 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	15 in. (38.1 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)/California only: 600 lb (272.2 kg)
Power Tilt Bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 16.9 gal (63.9 L) Under dash: 6 gal (22.8 L) Waterproof and removable box under passenger seat: 5.6 gal (21 L) Dash: 2 gal (7.7 L) Water-resistant and removable toolbox: 1.7 gal (6.3 L) Armrests and cup holders: 1.6 gal (6.1 L)
Towing Capacity	2,500 lb (1,134 kg)
Payload Capacity	1,630 lb (739 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	6

### FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, ECO™/ECO™ Off/Work modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Battery	12 V (30 A/h)
Magneto	650 W
Instrumentation	Lighter type DC outlets in the console (10 A) and two lighted USB ports in the dash storage (10 A)
Lighting	140 W lighting output from four 35 W reflectors ensuring wide visibility, signature LED and LED tail lights
Winch	Relocated 4,500 lb (2,041 kg) winch with synthetic rope and roller fairlead
Seat	Dual VERSA-PRO bolster bench seats for additional lateral support, passenger seats flipping up, adjustable driver seat, underside hooks, reinforced seat skin featuring X package trims and contoured bench to improve entrance/exit of the cab
Steering Wheel	Adjustable tilt steering
Protection	Heavy-duty front steel bumper, HMWPE full skid plate, aluminum rock sliders, mudguards
Hitch Type	2 in. hitch receiver

### WARRANTY & EXTENDED SERVICE

Factory Warranty	1 year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

© 2020 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. \*Smart-Lok was developed jointly with TEAM industries, a market leader in the drive train industry. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. All other trademarks are the property of their respective owners. ‡Top Speed limited to a maximum of 100 km/h (62 mph). For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SSVs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

