can-am. **MAVERICK SPORT X mr 1000R**

LICULICUTE

HIGHLIGHTS	
DARING	 Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	Easy handling and capabilitiesSuspension designed for performanceUltra-resistant chassis
CONFIDENT	Perfectly tunedEnhanced protectionMore adventure and less maintenance
PLATFORM FEATURES	• 90.6 in. wheelbase • 15 in. of ground clearance • 14.75 in. suspension travel • Dynamic Power Steering (DPS™) • SPORT/ECO™ modes • Premium half door • Mudguard
SPECIFIC TO X MR PACKAGE	• 64 in. wide with arched A-arm • Smart-Lok* front differential • Snorkeled engine air intake and CVT • FOX¹ 2.5 PODIUM¹ QS3 piggyback shocks • 30 in. ITP¹ Cryptid¹ tires • 14 in. cast-aluminum wheels • 4,500 lb (2,041 kg) winch with synthetic cable • Fender flare extensions

· X-package graphics/seats

	7.6 in. digital display with keypad Premium tail light
ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation. Strategically positioned CVT air intakes and exhaust. Lower gearing ratio and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/14.75 in. (37.5 cm) travel

TIRES	&	WHEELS	

Front Shocks

Rear Shocks

Rear Suspension

Front Tires	ITP Cryptid [‡] 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid [‡] 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

FOX 2.5 PODIUM piggyback

with QS3 compression adjustment Arched TTA with sway bar/14.75 in. (37.5 cm) travel

FOX 2.5 PODIUM piggyback

with QS3 compression adjustment

BRAKES	
Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers



1,617 lb (733.5 kg)

Profiled cage, ROPS approved

Iron Gray & Manta Green / 1000R

DIMENSIONS & CAPACITIES

Chassis/Cage

Estimated Dry Weight

LxWxH	122 x 64 x 74.25 in. (309.8 x 162.6 x 188 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	15 in. (38.1 cm)
Cargo Box Capacity	300 lb (136 kg)
Towing Capacity	1,500 lb (680 kg)
Storage Capacity	Total: 5.3 gal (20.2 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L)
Fuel Capacity	10 gal (38 L)
FEATURES	
Gauge	7.6 in. (19.3 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, front and rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Lighter type DC outlet in console (20 A)
Magneto	650 W
Lighting	Two 55 W reflectors with unique Can-Am LED signature and LED tail lights with halo glow effect
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper Premium half doors Full skid plate Mudguards Fender flare extensions Front tow hook
Hitch Type	2 in, hitch reveiver

EXTENDED SERVICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



