

can-am

MAVERICK X3 MAX DS TURBO R

2021

HIGHLIGHTS

DEFIANT	<ul style="list-style-type: none"> • Trademark Can-Am DNA with next generation design • Low seating position • Ergo-Lok cockpit with front and rear four-way adjustable seats
POWERFUL	<ul style="list-style-type: none"> • 172 hp turbocharged and intercooled Rotax[®] ACE engine • Advanced airflow dynamics • QRS-X transmission
PRECISE	<ul style="list-style-type: none"> • TTX suspension with industry-leading travel • Ultra efficient and lightweight chassis • Sharpest handling features
PLATFORM FEATURES	<ul style="list-style-type: none"> • 64 in. wide • 135 in. wheelbase • 14 in. of ground clearance • High torque Dynamic Power Steering (DPS™) • 20 in. suspension travel • FOX[†] 2.5 PODIUM[†] QS3 piggyback shocks • 14 in. aluminum wheels • 28 in. Maxxis[†] Bighorn 2.0[†] tires • 4.5 in. digital display with keypad • Rear tow hook
SPECIFIC TO DS TURBO R PACKAGE	<ul style="list-style-type: none"> • 172 hp Turbo R engine



- Octane Blue / TURBO R
- Can-Am Red / TURBO R
- Desert Tan & Carbon Black / TURBO R

ENGINE	TURBO R
Type	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTCT™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT with high-airflow, L/H/N/R/P
Drive Train	Selectable 2WD/4WD with Visco-Lok [†] auto-locking front differential
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/20 in. (50.8 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,726 lb (782.9 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	164 x 64 x 65.8 in. (416.6 x 162.5 x 167.1 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	13 in. (33 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights
Winch	N/A
Protection	Integrated front bumper Quarter-doors HMWPE full skid plate Rear tow hook

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months