

HIGHLIGHTS

- Rotax® V-Twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 3,500 lb (1,588 kg) winch
- 12 in. cast-aluminum wheels
- 26 in. Carlisle ACT HD 6-ply tires
- Heavy-duty front and rear bumpers
- Heated grips and throttle
- Front, central and footwell aluminum skid plates
- A-arms and TTI HMWPE protectors
- Torsional Trailing arm Independent (TTI) rear suspension
- Handlebar wind deflectors
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7 gal (21.4 L) water-resistant rear compartment



 Mossy Oak® Break-Up Country Camo / 650

ENGINE	650
Type	62 hp, Rotax 650 cc V-twin, liquid-cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/L, standard engine braking
Drive Train	Selectable 2WD/4WD with Visco-Lok [†] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	Oil

TIRES & WHEELS

Front Tires	Carlisle ACT HD 26 x 8 x 12 in.
Rear Tires	Carlisle ACT HD 26 x 10 x 12 in.
Wheels	12 in. cast-aluminum

BRAKES

Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES

Estimated Dry Weight*	749 lb (341 kg)
L x W x H	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES

Gauge	4.5 in. digital display: speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)
Anti-Theft System	N/A
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light
Winch	3,500 lb (1,588 kg) winch
Seat	Reinforced seat skin
Protection	Heavy-duty front and rear bumpers Front, central and footwell aluminum skid plates A-arm and TTI HMWPE protectors Heated grips and throttle Handlebar wind deflectors Mudguards

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months