

HIGHLIGHTS

- · Rotax® V-Twin engine
- Visco-4Lok† front differential
- Arched double A-arm front suspension with front sway bar
- 28 in. ITP Mega Mayhem tires
- 12 in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS)
- Intelligent Throttle Control (iTC™) with riding modes
- · Relocated radiator
- Heavy-duty front bumper
- · Mud-riding footrests
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- 650 W magneto
- X-package coloration, graphics and seat cover
- Mudguards



Desert Tan / 650

| ENGINE | 650 |
|----------------------|---|
| Туре | 62 hp, Rotax 650 cc V-twin, snorkeled, liquid-cooled with relocated radiator |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | CVT, P/R/N/H/L, standard engine braking |
| Drive Train | Selectable 2WD/4WD/Lock 4WD with Visco-4Lok front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |
| SUSPENSIONS | |
| Front Suspension | Arched double A-arm with front sway bar |
| Front Shocks | Oil |
| Rear Suspension | Torsional Trailing arm Independent (TTI) |
| Rear Shocks | Oil |
| TIRES & WHEELS | |
| Front Tires | ITP Mega Mayhem 28 x 8 x 12 in. |
| Rear Tires | ITP Mega Mayhem 28 x 10 x 12 in. |
| Wheels | 12 in. cast-aluminum |
| BRAKES | |
| Front | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm disc brake with hydraulic twin-piston caliper |

DIMENSIONS & CAPACITIES

| Estimated Dry Weight* | 874 lb (396 kg) |
|-----------------------|---|
| LxWxH | 88 x 48.5 x 50.5 in. (224 x 123 x 128 cm) |
| Wheelbase | 51 in. (129.5 cm) |
| Ground Clearance | 11.75 in. (29.9 cm) |
| Seat Height | 35.25 in. (89.5 cm) |
| Rack Capacity | Rear: 200 lb (90 kg) |
| Storage Capacity | Rear: 5.7 gal (21.4 L) |
| Towing Capacity | 1,650 lb (750 kg) |
| Fuel Capacity | 5.4 gal (20.5 L) |

FEATURES

| Gauge | 4.5 in. digital display: speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock |
|-------------------|---|
| Instrumentation | Lighter-type DC outlet in console, standard connector in the back (15 A) |
| Anti-Theft System | RF Digitally Encoded Security System (D.E.S.S.™) |
| Lighting | 230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light |
| Winch | Prewired for available winch |
| Seat | Standard |
| Protection | Heavy-duty front bumper Mud-riding footrests Mudguards |
| | |

WARRANTY & EXTENDED SERVICE

| Factory Warranty | 6-month BRP limited warranty |
|------------------------|---|
| Extended Service Terms | B.E.S.T. term available up to 36 months |

