

### HIGHLIGHTS

- Rotax® V-Twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Front and rear FOX<sup>†</sup> PODIUM<sup>†</sup> 1.5 RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- Front, center and footwell aluminum skid plates
- A-arms MWPE protectors
- 14 in. cast-aluminum beadlock wheels
- 26 in. ITP Terracross radial tires
- Aluminum sport bumper with aluminum pre-runner and top brace
- Aluminum taper-profile handlebar with full-wrap handguards
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 650 W magneto
- 5.7 gal (21.4 L) water-resistant rear compartment
- X package coloration



Chalk Gray & Magma Red / 1000R

ENGINE	1000R
Type	91 hp, Rotax 976 cc V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P/R/N/H/L, standard engine braking
Drive Train	Selectable 2WD/4WD with Visco-Lok <sup>†</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel
Front Shocks	FOX 1.5 PODIUM RC2
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel
Rear Shocks	FOX 1.5 PODIUM RC2

TIRES & WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in.
Rear Tires	ITP Terracross 26 x 10 x 14 in.
Wheels	14 in. cast-aluminum beadlock

BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS & CAPACITIES	
Estimated Dry Weight*	826 lb (375 kg)
L x W x H	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)
Wheelbase	51 in. (129.5 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Rear: 200 lb (90 kg)
Storage Capacity	Rear: 5.7 gal (21.4 L)
Towing Capacity	1,650 lb (750 kg)
Fuel Capacity	5.4 gal (20.5 L)

FEATURES	
Gauge	7.6 in. wide digital display: speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light
Winch	Prewired for available winch
Seat	Standard
Protection	Aluminum front bumper with pre-runner and top brace Aluminum taper-profile handlebar with full-wrap handguards Front, center & footwell aluminum skid plates A-arms HMWPE protectors Mudguards

WARRANTY & EXTENDED SERVICE	
Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months