

SHREDDER DS



ROTAX® ENGINE	850 E-TEC (3900 only)	850 E-TEC Turbo R	COLOR
			Platinum Silver Satin / Viper Red
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™	
Cylinders	2	2	
Displacement	849 cc	849 cc	
Bore	82 mm	82 mm	
Stroke	80.4 mm	80.4 mm	
Maximum engine speed	7,900 RPM	7,900 RPM	
Carburation	Electronic Direct Injection with additional booster injectors	Electronic Direct Injection with additional booster injectors	
Recommended fuel type	Unleaded	Unleaded	
Minimum octane	95	95	
Fuel tank	37 L / 9.8 gal		
Oil tank capacity (2-stroke)	3.4 L / 3.6 qt		
POWERTRAIN			DIMENSIONS
Gearbox			Overall vehicle length*
Drive clutch type	pDrive with clickers		3,250 mm / 128 in. (3900) 3,380 mm / 133 in. (4100)
Driven clutch type	QRS		Overall vehicle width
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, plastic master cylinder with protector		1,120 mm / 44 in.
			Overall vehicle height
			1,280 mm / 50,4 in.
			Ski stance
			921 mm / 36 in.
			Nominal track width
			381 mm / 15 in.
			Nominal track length
			3,912 mm / 154 in. 4,178 mm / 165 in.
			Track profile height
			3 in. PowderMax Light 2.5 in. PowderMax Light (option for 3900)
SUSPENSION			
Front suspension			LFS
Front shock			KYB 36 Kashima
Rear suspension			PPS ² -DS+ -3900 PPS ² -DS+ -4100
Center shock			KYB 36 Kashima
Rear shock			KYB 36 Kashima
FEATURES			
Frame	Radien ²	Reverse	RER
Skis	Blade DS+	Heated throttle lever	Standard
Seating	Shredder DS, 1-up	Heated grips	Standard
Handlebar	U-type aluminum with hooks, low grab handle	Gauge	4.5 in. digital display 10.25 in. color display with BRP Connect (option)
Riser block height	120 mm	USB power outlet	Yes, in front compartment
Starter	Manual with SHOT	LinQ attachment	2 pairs

*Overall vehicle length without snow flap.

©2022 Bombardier Recreational Products Inc., (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation.