

# 2023 MAVERICK X3 X<sub>RC</sub> TURBO RR 64"



■ Mineral Gray & Desert Tan / TURBO RR

ENGINE	TURBO RR
Type	200 hp, Rotax <sup>®</sup> ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4 modes traction system: 2WD/4WD with front diff. lock/4WD ROCK/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS™)

## SUSPENSIONS

Front Suspension	Double-arched A-arm with sway bar/18 in. (45.7 cm) travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/18 in. (45.7 cm) travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and bottom-out control

## TIRES & WHEELS

Front/Tires	Maxxis Liberty 30 x 10/10 x 14 in.
Wheels	14 in. cast-aluminum

## BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

## PACKAGE HIGHLIGHTS

- Smart-Lok<sup>®</sup> front differential
- FOX<sup>®</sup> 2.5 PODIUM QS3<sup>®</sup> piggyback shocks
- Belt monitoring system
- 850 W magneto
- 7.6 in. digital display with keypad
- X-package graphics/seats
- Can-Am LED signature
- 30 in. Maxxis Liberty<sup>®</sup> tires
- Front bumper, quarter-doors
- Front tow hook
- 4,500-lb (2,041 kg) winch with synthetic rope
- HMWPE differential and under bumper skid plates
- HMWPE front and rear suspension arm
- UHMWPE rock sliders

## DIMENSIONS & CAPACITIES

Estimated Dry Weight	1,674 lb (759.3 kg)
Chassis/Cage	Dual-phase 980 steel
L x W x H	133 x 65.6 x 66 in. (337.8 x 166.6 x 167.6 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	14 in. (35.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ <sup>®</sup> Quick-Attach
Storage Capacity	Total: 2.5 gal (9.4 L)
Fuel Capacity	10.5 gal (40 L)

## FEATURES

Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlight, LED signature, LED tail lights
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper, quarter doors, UHMWPE rock sliders HMWPE skidplates: full heavy-duty with differential/under bumper/front and rear suspension arm, rear tow hook

## WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service	B.E.S.T. term available up to 30 months
Terms	

© 2022 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 1 Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) operator's guide and watch the Safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SSVs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. \*Smart-Lok was developed in conjunction with TEAM industries, a market leader in the drive train industry.

